

IBM Support



Overview - IBM Ultra-Nav Keyboards for IBM System x

Product Documentation

Abstract

Overview of IBM Ultra-Nav Keyboards for IBM System x

Content

Overview

The Ultra-Nav keyboards are now available for use with IBM System x systems. These lower-cost products are RoHS 7cIII compliant and are replacing current similar products.

At a glance

The new Ultra-Nav keyboards are RoHS 7cIII compliant.

Key benefits:

- Lower cos
- RoHS 7cIII compliant

Marketing and replacement part number information

IBM Keyboard w/ integrated pointing device USB		
Country/Language	Marketing part number	Replacement part number (FRU/FAP)
US English 103P RoHS	94Y6179	94Y6108
LA Spanish 171 RoHS	94Y6195	94Y6124
French/Canada 445 RoHS	94Y6187	94Y6116
Arabic 253 RoHS	94Y6180	94Y6109
Belgium/UK 120 RoHS	94Y6181	94Y6110
Czech 489 RoHS	94Y6183	94Y6112
Danish 159 RoHS	94Y6184	94Y6113

Contact and feedback

IBM Keyboard w/ integrated pointing device USB		
Dutch 143 RoHS	94Y6185	94Y6114
French 189 RoHS	94Y6186	94Y6115
German 129 RoHS	94Y6188	94Y6117
Greek 219 RoHS	94Y6189	94Y6118
Hebrew 212 RoHS	94Y6190	94Y6119
Hungarian 208 RoHS	94Y6191	94Y6120
Italy/Italian 141 RoHS	94Y6192	94Y6121
Norwegian 155 RoHS	94Y6196	94Y6125
Polish 214 RoHS	94Y6197	94Y6126
Portugese 163 RoHS	94Y6198	94Y6127
Russian 441 RoHS	94Y6199	94Y6128
Slovak 245 RoHS	94Y6200	94Y6129
Spanish 172 RoHS	94Y6201	94Y6130
Swed/Finn 153 RoHS	94Y6202	94Y6131
Swiss F/G 150 RoHS	94Y6203	94Y6132
Turkish 179 RoHS	94Y6205	94Y6134
UK English 166 RoHS	94Y6206	94Y6135
US Euro 103P RoHS	94Y6207	94Y6136
Slovenian 234 RoHS	94Y6208	94Y6137
Chinese/US 467 RoHS	94Y6182	94Y6111
Japanese 194 RoHS	94Y6193	94Y6122
Korean 413 RoHS	94Y6194	94Y6123
Thai 191 RoHS	94Y6204	94Y6133

Contact and feedback

Key prerequisites

A selected IBM System x server requiring a keyboard.

Agency approvals

- EN55022
- EN55024
- EN60950-1
- EN 61000-3-2
- EN 61000-3-3
- IEC 60950-1
- FCC Part 15 Class A
- UL 60950-1
- CSA C22.2 60950-1-07
- VCCI
- NZ AS3548 / C-tick
- RRL for MIC (KCC)
- BSMI (EMC)
- IECS-003:2004 Issue 4

Operating environment

- Temperature: Operating
 - 0 to 55 degrees C (-32 to 131 F) at 0 to 914 m (0 to 3,000 ft)
 - 10 to 32 degrees C (50 to 90 degrees F) at 914 to 2133 m (3,000 to 7,000 ft)
- Relative humidity: 20% to 80% (noncondensing)
- Maximum altitude: 2,133 m (7,000 ft)
- Air flow: 200 LFM at 55 degrees C

Hardware requirements

A selected System x server system.

Compatibility:

- ServerProven testing, which verifies servers and keyboard and mouse products will function properly
For latest compatibility information, visit
<http://www.ibm.com/servers/eserver/serverproven/compat/us/>

Note: Some configurations may not be compatible.

Warranty

- One year limited warranty

For information on the IBM Statement of Limited Warranty, visit

<http://www.ibm.com/systems/support/supportsite.wws/warrantyform?brandind=5000008>

Alternatively, this information is available through your IBM representative or reseller. Copies are available upon request.

Applicable countries and regions

- Worldwide

Document Information

More support for:

System x Hardware Options->Keyboard - USB->Integrated pointing device->94Y6195

Document number:

807782

Modified date:

24 January 2019